


**HT-320F**
**HT-66**
**HT-68**
**HT-69**
**HT-69A**

<b>Model No.</b>	<b>HT-320F</b>	<b>HT-66</b>	<b>HT-68</b>	<b>HT-69</b>	<b>HT-69A</b>
<b>Parameter</b>					
Capsule Type	Condenser	Condenser	Condenser	Condenser	Condenser
Frequency Response	20Hz-20kHz	40Hz-18kHz	50Hz-18kHz	30Hz-18kHz	30Hz-18kHz
Polar Pattern	Super Cardioid	Uni-Directional	Uni-Directional	Uni-Directional	Uni-Directional
Output Impedance	75 Ohm	75 Ohm	75 Ohm	75 Ohm	75 Ohm
Sensitivity (±2dB)	-40dB	-38dB	-40dB	-40dB	-40dB
Power Supply	Phantom Power 48V	Phantom Power 48V	Phantom Power 48V	Phantom Power 48V	Phantom Power 48V
N.W.	0.11kg	0.33kg	0.33kg	0.33kg	0.33kg
Sound Pick-up Distance	3 m	1 m	1 m	1 m	1 m
Dimension mm	Diameter 30 Length 170	Diameter 45 Length 200	Diameter 45 Length 200	Diameter 45 Length 200	Diameter 45 Length 200
Output	Balance	Balance	Balance	Balance	Balance