



HT-F12/2

HT-F8/2

Professional Mixer

Model No. Parameter	HT-F8/2	HT-F12/2
Input Power	AC 220V 50~60Hz	AC 220V 50~60Hz
Max Output Level	19dBm (1Hz, THD=0.5%)	19dBm (1Hz, THD=0.5%)
S/N	71dB	71dB
Headphone Output Consumption	40mw (1Hz, THD=0.5%, 200 Ohm)	40mw (1Hz, THD=0.5%, 200 Ohm)
Frequency Response	20Hz-20kHz	20Hz-20kHz
N.W.	4.41 kg	5.57 kg
Dimension (L×W×H)mm	400×400×45	443×400×45
Consumption	25W	35W
Input Type	XLR×4/REC×4	XLR×8/REC×4
T.H.D.	=0.05% (1kHz, 0.775V)	=0.05% (1kHz, 0.775V)
Color	Grey	Grey

Time Sequence Power Controller

- ◆ Input Power: AC 220V 50~60Hz
- ◆ Power Capability: 220V, 16A, Max 10A/channel
- ◆ Control Channel: 8 channel
- ◆ Interval Time: 1.5 Secs
- ◆ Dimension (L×W×H): 430mm×260mm×44mm
- ◆ N.W: 3.42kg



HT-3208